



Technical Specifications

Dimension	W 9.33" x H 35.50" x D 9.65"	
	(W 237 x H 902 x D 245 mm)	
Fare media acceptance	Coins: U.S. 1¢, 5¢, 10¢, 25¢, 50¢, \$1	
	Bills: U.S. \$1, \$2, \$5, \$10, \$20	
	Option: Tokens	
Cashbox capacity	Coins: 400 in ³ (6.6 L) \$500 or 2,000 coins, whichever is smaller	
	Bills: 330 in ³ (5.5L) \$800	
Passenger display	TFT RGB 3.5" color display	
	QVGA 320 x 240 pixels	
OCU (Operater control unit)	Resistive touch screen TFT RGB 5.0" color display	
	WVGA 800 x 480 pixels	
Communication Interface	Standard: J1708 x 1, RS422 x 1, Ethernet x 2, USB x 2 (internal)	
Power Supply	Rated: 12 VDC or 24 VDC	
	Operating range: 10 VDC to 36 VDC	
	Max. current draw at 12 VDC: Peak 3.0 A, Idle 1.6 A, sleep 0.8 A	
Weights	Farebox: 88 lb (40.1 kg) (with Cashbox)	
	Cashbox: 15 lb (6.7 kg)	
Materials	Farebox: 304 stainless steel 14 GA (2.0 mm)	
	Cashbox: 304 stainless steel 20 GA (1.0mm)	
Environmental	Operating Temperature: +32° F to +122° F(0° C to 50° C)	
	Storage Temperature: -25° F to +140° F(-32° C to 50° C)	



Simplified revenue collection using RFID key-card.



Modular design for easy maintenance.



Built-in Touch Screen OCU saves space.

LECIP INC.